Date of Response: November 5, 2007 Final Office Action Dated: April 3, 2007

RECEIVED CENTRAL FAX CENTER

Amendments to the Claims:

NOV 0 6 2007

This listing of claims will replace all prior versions and listings of claims in the application:

- 1.-11. (Cancelled)
- 12. (Currently Amended) The apparatus of Claim 1 An apparatus for enclosing goods on a surface for treatment comprising:

a canopy that is substantially impermeable to flowable materials;

an upper perimeter for supporting an upper portion of said canopy:

a lower perimeter for supporting a lower portion of said canopy, said lower perimeter being moveable with respect to said upper perimeter to form a chamber:

a perimeter support for supporting said upper perimeter and lower perimeter; and

a gasket in communication with said lower perimeter, said gasket being deformable to substantially seal the chamber by compressing said gasket against the surface and wherein the gasket has a hollow portion along its length and an inner surface in communication with the chamber, the inner surface having a plurality of perforations extending from the chamber to the hollow portion of the gasket.

- 13. (Original) The apparatus of Claim 12 further comprising a flowable material supply in communication with the hollow portion of the gasket.
- 14. (Original) The apparatus of Claim 12 wherein the flowable material supply is a cold air supply.
- 15.-26. (Cancelled)
- 27. (Currently Amended) The method of Claim 25 A method of treating goods with a flowable material comprising the steps of:

placing the goods on a surface;

Page 3 of 10

PHILI 758473-1

Date of Response: November 5, 2007 Final Office Action Dated: April 3, 2007

providing an apparatus comprising:

a canopy that is substantially impermeable to the flowable material:

an upper perimeter for supporting an upper portion of said canopy:

a lower perimeter for supporting a lower portion of said canopy:

a perimeter support for supporting said upper perimeter and lower perimeter; and

a gasket in communication with said lower perimeter, said gasket being deformable and wherein the gasket has a hollow portion along its length and an inner surface in communication with the chamber, the inner surface having a plurality of perforations extending from the chamber to the hollow portion of the gasket,

lowering the apparatus to form a chamber over said goods on said surface;

causing the gasket to deform against said surface to substantially seal the chamber;

treating the goods comprising injecting the flowable material into the chamber wherein and the step of injecting the flowable material into the chamber further comprises connecting a flowable material supply to the hollow portion of the gasket; and

venting the chamber.

- 28.-39. (Cancelled)
- 40. (Currently Amended) The apparatus of Claim 30An apparatus for enclosing goods on a surface for fumigation comprising:

a canopy that is substantially impermeable to flowable materials; an upper perimeter for supporting an upper portion of said canopy;

a lower perimeter for supporting a lower portion of said canopy, said lower perimeter to be placed in proximity to said surface:

Page 4 of 10

PHILL 758473-1

Date of Response: November 5, 2007 Final Office Action Dated: April 3, 2007

a support structure capable of supporting said upper perimeter and lower perimeters; and

a gasket in communication with said lower perimeter, wherein said gasket is capable of being compressed by said lower perimeter against said surface to form a chamber, wherein the gasket has a hollow portion along its length and an inner surface in communication with the chamber, the inner surface having a plurality of perforations extending from the chamber to the hollow portion of the gasket.

- 41. (Original) The apparatus of Claim 40 further comprising a flowable material supply in communication with the hollow portion of the gasket.
- 42. (Original) The apparatus of Claim 41 wherein the flowable material supply is a cold air supply.
- 43.-55. (Cancelled)
- 56. (Currently Amended) The apparatus of Claim 46 An apparatus for enclosing produce on a surface for furnigation and re-cooling comprising:

a canopy that is substantially impermeable to flowable materials; an upper perimeter for supporting an upper portion of said canopy;

a lower perimeter for supporting a lower portion of said canopy, said lower perimeter being moveable with respect to said upper perimeter to form a chamber;

a perimeter support for supporting said upper perimeter and lower perimeter;

a gasket in communication with said lower perimeter, said gasket being deformable to substantially seal the chamber by compressing said gasket against the surface;

a fumigation conduit for injecting a flowable material into the chamber;

a vent to release the flowable material from the chamber;

Page 5 of 10

PHILI 758473-1

Date of Response: November 5, 2007 Final Office Action Dated: April 3, 2007

a means for changing a pressure within the chamber; and

a cooling conduit for supplying chilled air to the chamber, wherein the cooling conduit forms a bore along the length of said gasket, the cooling conduit having an inner surface in communication with the chamber, the inner surface having a plurality of perforations extending from the chamber to the cooling conduit.

57.-63. (Cancelled)

64. (Currently Amended) The method of Claim 63 A method of fumigating and recooling produce comprising the steps of:

placing the produce on a surface;

providing an apparatus comprising:

a canopy that is substantially impermeable to flowable materials;

an upper perimeter for supporting an upper portion of said canopy;

a lower perimeter for supporting a lower portion of said canopy;

a perimeter support for supporting said upper perimeter and lower perimeter;

a gasket in communication with said lower perimeter, said gasket being deformable;

lowering the apparatus to form a chamber over said produce on said surface;

causing the gasket to deform against said surface to substantially seal the chamber;

injecting a first flowable material into the chamber to furnigate the produce;

Page 6 of 10

PIULI 758473-1

and

DV. 6.2007 3:27PM KLEHR,HARRISON,ETLA NO.354 P.12/15

Applin No. 09/871,774

Date of Response: November 5, 2007 Final Office Action Dated: April 3, 2007

venting the first flowable material from the chamber:

creating a first negative pressure within the chamber; and

supplying a second flowable material to the chamber for re-cooling the produce, wherein the second flowable material is supplied to the chamber via a cooling conduit in communication with the chamber and wherein the cooling conduit forms a bore along the length of said gasket, the cooling conduit having an inner surface in communication with the chamber, the inner surface having a plurality of perforations extending from the chamber to the cooling conduit, and the step of supplying the second flowable material further comprises connecting a chilled air supply to the cooling conduit.

65.-66. (Cancelled)